

CHI MEI CORPORATION

59-1 SAN CHIA JEN TE TAINAN HSIEN TAIWAN

Material Designation: **PM-600**

Product Description: Methylmethacrylate/Styrene (MMA/S), designated "Acrystex" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5-1.7	HB	5	2	50	50	50	-	-
CTI: 2	IEC CTI: -	HVTR: 2			D495: 6			IEC Ball Pressure (°C): -	
Dielectric Strength (kV/mm): - ISO Tensile Strength (MPa): - ISO Tensile Impact (kJ/m²): -		Volume Resistivity (10⁹ohm-cm): - ISO Flexural Strength (MPa): - ISO Izod Impact (kJ/m²): -				Dimensional Stability(%): - ISO Heat Deflection (°C): - ISO Charpy Impact (kJ/m²): -			

Report Date: 8/15/2003

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.